

SLUDGE AWAY™

RE-LIQUEFIER & REMOVER



PRODUCT DETAILS

Sludge Away™ is a powerful combination of organic and petroleum solvents that will quickly break down asphaltics and asphaltenes that settle out of fuels and fuel oils and congregate at the bottom of the tank as a thick clogging sludge. Sludge Away™ causes the fuel to reabsorb and hold these components in suspension until they can be burned. Sludge Away™ causes fuel to be atomized better by the burners for more efficient combustion and reduced emissions.

SLUDGE AWAY™ SLOWS THE OXIDATION OF FUEL, STABILIZING IT AND CONTAINS NO HARMFUL ALCOHOLS THAT CAN DAMAGE GASKETS AND SEALS.

Sludge Away™ chemically removes the water found in all heating fuels. Water that can corrode metal parts, water that mixes with the sulfur in fuel to create damaging sulfuric acid, water that can freeze in filters and fuel lines, water that supports the growth of spores and bacteria into a thick sticky slime that clogs fuel burner nozzles and plugs fuel filters. By eliminating water, you can prevent all of these problems.

With today's Hi-Tech electronically controlled burners, the need to make older equipment last longer, the need for a high quality fuel treatment is more important than ever before.

KEY BENEFITS

- Breaks down Sludge found at the bottom of fuel tanks
- Will break down fuel line clogs caused by sludge
- Reabsorbs and holds in suspension so that fuel will not plug filters
- Cleans Fuel Burner Nozzles and Pumps
- Reduces Oxidation to Stabilize Fuel
- Eliminates Water
- Organic Based Formula with No Harmful Alcohols
- Improves Fuel Atomization for Greater Efficiency and Reduced Emissions



PEAK PERFORMANCE CLEAN BURNING TECHNOLOGY

- ✓ ADVANCED FORMULAS
- ✓ INDUSTRY EXPERTS
- ✓ SUPERIOR PERFORMANCE
- ✓ INCREASE ECONOMY
- ✓ PROFESSIONAL SERVICES

CORONA™ RATIO - 1:2400

P/N	SIZE	TREATS
11124	16 oz.	300 gallons
11126	1 gallon	2,400 gallons
11127	5 gallons	12,000 gallons
11129	55 gallons	132,000 gallons
11120	275 gallons	600,000 gallons

SLUDGE AWAY™ RATIO - 1:4000

P/N	SIZE	TREATS
11114	32 oz.	1,000 gallons
11116	1 gallon	4,000 gallons
11117	5 gallons	20,000 gallons
11119	55 gallons	132,000 gallons
11110	275 gallons	1,100,000 gallons



SUPERIOR HI-TECH TREATMENT & CONDITIONING FOR HOME HEATING OIL



CORONA™

HEATING OIL TREATMENT

PRODUCT DETAILS

Corona™ is the All-Season Treatment to Improve Fuel Efficiency, Stabilize Fuel, Prevent Fuel Gelling, and Eliminate the Harmful Effects of Water in the Fuel.

Corona™ is an organic based product that is a powerful fuel system and burner cleaner. It dissolves the gum, varnish, and carbon deposits that distort fuel burner spray patterns and damage delicate pump components. Cleaning these parts allows your burner to operate with all the efficiency that the manufacturer designed into it. Corona™ causes fuel to be atomized better by the burners for more efficient combustion and reduced emissions. Corona™ slows the oxidation of fuel, stabilizing it.

CORONA™ CONTAINS NO HARMFUL ALCOHOLS THAT CAN DAMAGE GASKETS AND SEALS.

Corona™ chemically removes the water found in all heating fuels. Water that can corrode metal parts, water that mixes with the sulfur in fuel to create damaging sulfuric acid, water that can freeze in filters and fuel lines, water that supports the growth of spores and bacteria into a thick sticky slime that clogs fuel burner nozzles and plugs fuel filters. By eliminating water, you can prevent all of these problems.

Corona™ has a powerful Anti-Gel with a cold flow improver wax modifiers that will prevent fuel from gelling down to as low as -35°F. Corona will help hold wax in suspension, slowing the growth of crystals that plug filters in cold weather.

With today's Hi-Tech electronically controlled burners, the need to make older equipment last longer, the need for a high quality fuel treatment is more important than ever before.

Corona's™ highly concentrated formula uses only 16 ounces to treat 300 gallons.

For Maximum Protection and Smoother Performance, Depend on Corona™.

THE ALL-SEASON, HI-TECH TREATMENT AND CONDITIONER FOR TODAY'S HEATING OIL.

KEY BENEFITS

- Cleans Fuel Burner Nozzles and Pumps
- Reduces Oxidation to Stabilize Fuel
- Eliminates Water
- Powerful Anti-Gel
- Organic Based Formula with No Harmful Alcohols
- Improves Fuel Atomization for Greater Efficiency and Reduced Emissions
- Inhibits Fuel Tank Corrosion
- Just 16 oz. treats up to 300 gallons

DIRECTIONS

For best results, use every time you add fuel, adding contents to fuel tank prior to fueling. The fueling process will ensure that complete and proper mixing takes place. Use 16 ounces for each 300 gallons of fuel (1:2400 treatment ratio). First time users can use 16 ounces for each 150 gallons to speed the cleaning process. When operating in extreme conditions (high humidity, very cold weather) it is acceptable to use the 16 ounces per 150 gallons dosage on a regular basis. Corona™ will eliminate its own volume of water.

For more information please consult the Material Safety Data Sheet for this product.

